

SPECIFICATIONS

Model	Strategy iES16		Strategy iES32	
Capacities	Minimum configuration 4 ports, expandable in 4-port increments to 16 ports via electronic upgrade. Message storage 100 hours. Unlimited mailboxes.		Minimum configuration 4 ports, expandable in 4-port increments to 32 ports via electronic upgrade. Message storage 600 hours. Unlimited mailboxes.	
Chassis Measurements	Width	Height	Depth	Weight
Metric	33 mm	191 mm	152 mm	.4 kg
English	1.3 in.	7.5 in.	6 in.	.8 lbs.
Power Supply Unit (PSU)	Uses hosting Strata CIX power supply			
Primary AC Power	Input AC 120VAC, 4.0 amps maximum. AC Frequency Single-phase (48Hz - 62Hz).			
Power Backup	Provided by the power backup of the hosting Strata CIX chassis			
Cooling	Convection		Processor fan	
Operating Temperature	39~104° F (4~40° C)			
Operating Humidity	20~80% relative humidity without condensation			
Storage Temperature	-4~140° F (-20~60° C)			
Chassis Installation	Printed circuit board installs in card slot in Strata CIX100, CIX200, or CIX670 chassis.			
Compliance	Safety: UL EMC: FCC Part 15 Class A (Subpart J)			
Data Storage Media	Compact Flash 2GB		Hard drive 10GB	
CPU	Intel Pentium II 333Mhz processor			
Memory	256MB			
Operating System	Microsoft Windows NT Embedded Workstation			
Voice Resources	On-board (16 channels maximum)		On-board (32 channels maximum)	
Modem	Internal soft modem 36.6Kbps			
Communication Ports	One RS-232 COM port			
Network Interface Connection	One 10/100BaseT Network Interface Connection			
Connection to Strata CIX	Direct backplane in slot in Strata CIX chassis			
Remote Access	Modem, NetMeeting, Windows NT RAS.			
Standard Applications	Strategy Voice Mail, Auto Attendant, Token Programming, 5-seat Unified Messaging			
Optional Applications	Strategy ES feature groups include additional Unified Messaging seats, Text-to-Speech, Fax Applications. Interactive Voice Response capabilities available via Token Programming or custom development.			
Application Installation	All feature group application software is pre-installed and activated electronically through license control. IVR capabilities deployed by Authorized Toshiba Dealers.			