

<b>SPECIFICATIONS</b>				
Model	Strategy IVP8			
Capacities	Minimum configuration 2 ports, expandable to 4, 6, or 8 ports via electronic upgrade. Message storage 15 hours, upgradeable to 30 hours. Unlimited mailboxes.			
Chassis Measurements	Width	Height	Depth	Weight
Metric	33 mm	191 mm	152 mm	.4 kg
English	1.3 in.	7.5 in.	6 in.	.8 lbs.
Power Supply Unit (PSU)	Uses hosting Strata CIX power supply			
Primary AC Power	Input AC 120VAC, 4.0 amps maximum. AC Frequency Single-phase (48Hz - 62Hz).			
Power Backup	Provided by the power backup of the hosting Strata CIX chassis			
Cooling	Convection			
Operating Temperature	39~104° F (4~40° C)			
Operating Humidity	20~80% relative humidity without condensation			
Storage Temperature	-4~140° F (-20~60° C)			
Chassis Installation	Printed circuit board installs in card slot in Strata CIX100, CIX200, or CIX670 chassis.			
Compliance	Safety: UL EMC: FCC Part 15 Class A (Subpart J)			
Data Storage Media	Compact Flash 256MB, upgradeable to 512MB			
CPU	Embedded			
Memory	4MB			
Operating System	ROM DOS			
Voice Resources	On-board (8 channels maximum)			
Modem	Internal soft modem 14.4k baud			
Communication Ports	Two RS-232 COM ports			
Connection to Strata CIX	Direct backplane in slot in Strata CIX chassis			
Remote Access	Modem			
Standard Applications	Strategy Voice Mail, Auto Attendant, Token Programming.			
Optional Applications	IVR capabilities available via Token Programming or custom development.			
Application Installation	Deployed by Authorized Toshiba Dealers.			