

**SPECIFICATIONS**

Model	Strata Media Application Server			
Capacities	Up to 32 HMP ports assigned as either 32 voice mail ports, 32 ACD ports, or 16 voice mail ports and 16 ACD ports. Voice Mail message storage up to 5,000 hours.			
Chassis Measurements	Width	Height	Depth	Weight
Metric	430 mm	43 mm	609 mm	13.6 kg
English	16.9 in.	1.7 in.	23.9 in.	30 lbs.
Power Supply Unit (PSU)	Initially Built-in			
Primary AC Power	Input AC 120VAC, 5.67 amps maximum. AC Frequency Single-phase (50Hz - 60Hz). 680 watts per cabinet (maximum).			
Power Backup	Uninterruptible Power Supply (UPS) is required for power backup similar to the ones used for computer systems and networking equipment.			
Cooling	Six rotary fans			
Operating Temperature	50°~95°F (10~35°C)			
Humidity	Non-Operating: 45% non-condensing at 86°F (30°C)			
Storage Temperature	-40°~ 158°F (-40~ 70°C)			
Chassis Installation	19" Rack-mount			
Compliance	Safety: UL/CSA 60950-1:2003 (UL RecognitionMark) EMI Verification: Verified to FCC, Class A			
Data Storage Media	80GB Hard Drive			
CPU	2.4 Ghz Pentium 4			
Memory	512MB RAM (Standard); 2 gigabyte maximum			
Operating System	Microsoft Windows XP Professional			
Voice Resources	Host-based Media Processing (HMP)			
Modem	Optional USB Modem for remote administration			
Network Interface	1x1000/100/10Mbit, 1x100/10Mbit			
Connection to Strata CIX	Single Ethernet IP connection through a network switch			
Remote Access	Remote access via the network using the Windows® XP Remote Desktop feature			
Standard Applications	4-port Strategy ES Voice Mail with Auto Attendant, Token Programming, and 5-seat Unified Messaging. eManager browser-based system administration. My Phone Manager browser-based personal administration.			
Optional Applications	Additional Strategy ES ports up to maximum 32. Strategy ES feature groups (additional Unified Messaging seats, Automated Speech Recognition, Text-to-Speech). Interactive Voice Response capabilities available via Token Programming or custom development. Strata Automatic Call Distribution (ACD) and OASYS modules. Insight or TASKE ACD Reporting. Info Manager Web-based telephone applications. FeatureFlex adaptability/customization tools.			
Application Installation	All application software is pre-installed. Optional applications and Strategy ES feature groups activated through license control. IVR capabilities deployed by authorized Toshiba Dealers.			